

## RLS

### Technical Data Sheet



SYMBOL	pH
DP-05	7

Professional & advanced product for reloading ceramic quartz coatings. Slick & hydrophobic effect. Protection for car paint and glass. Enhanced colour.

#### **APPLICATION:**

- ceramic-quartz coatings, car paint

#### **COMPOSITION:**

- alcohols
- solvents
- auxiliary substances

#### **USAGE:**

Perform the whole operation at room temperature (~25°C).  
Spray evenly onto clean and dry surface. Buff with microfiber towel.

Warning: Never perform this operation in full sun or on the heated surface.

#### **CLASSIFICATION OF THE MIXTURE:**



## RLS

### Technical Data Sheet

**Signal words:**

DANGER

**Hazard statements:**

- H225** – Highly flammable liquid and vapour.
- H304** – May be fatal if swallowed and enters airways.
- H319** – Causes serious eye irritation.
- H336** – May cause drowsiness or dizziness.

**Precautionary statements:**

- P210** – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P271** – Use only outdoors or in a well-ventilated area.
- P301+P310** – IF SWALLOWED: Immediately call a POISON CENTER/doctor.
- P331** – Do NOT induce vomiting.
- P405** – Store locked up.

**SELL-BY DATE:**

36 months from the production date.

Production date/series and expiration date are stated on the packaging.

**ADDITIONAL INFORMATION:**

Additional information can be found in safety data sheet.

Contaminated containers should be completely emptied. Several times rinse the container promptly after emptying. Empty container can be stored in containers for collection of plastic packaging, or can be delivered to specialized company for recycling.

Disposal should be in accordance with the national/international regulations