

## SLS

### Technical Data Sheet



SYMBOL	pH
DP-04	8

Professional cream for finishing car paint protected with ceramic quartz coating. Reloads coatings and creates hydrophobic, extra-slick & durable finishing layer.

#### **APPLICATION:**

- car bodies (quartz-ceramic coatings, car paint)

#### **COMPOSITION:**

- < 20% alcohol
- < 5% non-ionic surfactants
- auxiliary substances not classified as dangerous

#### **USAGE:**

Apply indoor if possible, with temperature of 18-24°C. Make soor the surface is clean and cool. Spread evenly with applicator. Buff with microfiber cloth.

Hardening time minimum 4 hours.

Warning: Do not use on heated surfaces and in full sun.

#### **CLASSIFICATION OF THE MIXTURE:**

*SLS*

## **Technical Data Sheet**



**Signal words:**  
DANGER

**Hazard statements:**  
**H226** – Flammable liquid and vapour.

**Precautionary statements:**  
**P210** – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

***SELL-BY DATE:***  
36 months from the production date.  
Production date/series and expiration date are stated on the packaging.

***ADDITIONAL INFORMATION:***  
Additional information can be found in safety data sheet.

Contaminated containers should be completely emptied. Several times rinse the container promptly after emptying. Empty container can be stored in containers for collection of plastic packaging, or can be delivered to specialized company for recycling.

Disposal should be in accordance with the national/international regulations